



Food Display & Storage Specialists

IN STOCK NOW FOR FAST DELIVERY

Profit from Our Experience. Full automatic defrost. Excellent product visibility with diffused LED lighting.

LIEBHERR

Display & Storage Refrigeration

Introducing the SGT 1322 Freezer

- Low energy consumption and low maintenance
- Environmentally friendly refrigerant
- Easy-glide glass lids
- Contoured front and robust metal handles
- Remote cabinet monitoring possible



*other models / sizes available including dual temperature variants

03330 147 888


home.liebherr.com

LGB.RefrigerationSales@liebherr.com

SGT 1322 Freezer

LED

Gross/net capacity

Fridge compartment	-/- litre
Freezer compartment	1290/905 litre
Ext. dimensions in mm (w/d/h)	2500/1050/1008
Int. dimensions in mm (w/d/h)	2265/800/550
Total display surface area (TDA)	1.76
Energy efficiency class	
Energy consumption in 365 days	1808 kWh
Climate rating/Temperature class	3 / L1
Ambient temperature range	+16°C to +25°C ¹
Refrigerant	R 290
Filling quantity refrigerant	115 g
Noise output	62 dB(A)
Connection Rating	4.5 A
Frequency/voltage	50 Hz / 220-240 V~

Cooling system	static
Defrosting	auto hot-gas defrost
Temperature range	-19°C to -21°C
Housing material/colour	Composite/white
Lid material	Sliding glass lid
Liner Material	aluminium
Type of Control	Touch-electronic
Temperature display	external digital
Interior light	LED
Fault: warning signal	visual
Interface	CAN-BUS
Adjustable dividers	5+1
Connecting cable length	2.3 m
Gross/net weight	206/175 kg
EAN-Nr.	9005382192795



¹ Indicates the ambient temperature at which the device can be operated safely.

Subject to modification. Timestamp: 09.11.2021